

Specifications:

Current rating:1.0A AC/DC

Voltage rating:12V AC/DC

Contact resistance: 20m ohm max

Insulation resistance: 100M ohm. min.

Withstanding voltage:250V AC for one minute

Operating temperature range:-40°C to +105°C

Material and Finish:

Insulator:High Temp. Plastic(UL94V-0)

Insulator Color:Black

Contact:Copper Alloy


Shell:Brass With Nickel Plated

Plating:Selective Gold Plated

How To Order

1201-XX-5M

Full Shielding
No. of Contacts



ARRANGMENT OF CONTACT						
NO. OF CONTACT	3	4	5	6	7	8
PRODUCT NO.	1201-03-5M	1201-04-5M	1201-05-5M	1201-06-5M	1201-07-5M	1201-08-5M
P.C.B.LAYOUT (BOTTOM VIEW)						

				DRAWN: Cel King	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15	 繼德工業股份有限公司 Neltron Industrial Co., Ltd.	DESCRIPTION: Mini Din Jack PCB Type Side Entry	SIZE A4
E				CHECKED: Jeremy Liu	UNIT: MM			
D				APPROVAL: Mike Wu	SCALE:	PART NO: 1201-XX-5M		
C					SHEET: 1 / 1			
B	04-Apr-2006	ECN-CN060403	Cel King		PROJECTION: 			
A	02-OCT-2005	(PC0004)	DXS					
REV	DATE	FILE	BY					